

Link do produktu: <https://sosos.pl/io-extender-hdmi-50m-cat638205-lindy-p-35173.html>



I/O Extender Hdmi 50M CAT6/38205 Lindy

Cena	708,01 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1350850
Kod EAN	4002888382052
Jednostkowa waga netto	0.307 kg
CnCode	85176200
Głębokość opakowania wysyłkowego	22 cm
Waga opakowania wysyłkowego	0.64 kg
Unit Box Width	0.135
Unit Box Height	0.07
Objętość jednostki brutto	3
Micro-USB	2
ManufacturerCode	38205
Ilość w opakowaniu	1
Jednostkowa waga brutto	0.64 kg
Category Code	IOC
Szerokość opakowania wysyłkowego	13.5 cm
Wysokość opakowania wysyłkowego	7 cm
Unit Box Length	0.22
Kolor	Czarny
RJ46	2
Strona główna dostawcy	www.lindy-international.com/50m-Cat-6-HDMI-4K60-IR-Extender-with-PoC-Loop-Out.htm?websale8=ld0101.ld021102&pi=38205&ci=20
Objętość brutto	0.002079 cubm

Opis produktu

50m Cat.6 HDMI 4K60 & IR Extender with PoC & Loop Out

- Amplify HDMI 18G & IR signals over 50m via Cat.6 cable

-
- Extends 4K HDMI 18G signals over 50m distances with standard network cable
 - Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit, with support for HDR
 - An HDMI loop-through output creates an additional viewing zone with a local display
 - PoC (Power over Cable) functionality for power from a single power supply

The Lindy Cat.6 HDMI 4K60 & IR Extender with PoC is an effective, reliable solution for extending high quality 4K HDMI signals over distances up to 50m (164.04ft) with standard Cat.5e/6 network cable. Support for the HDMI 2.0 18G specification allows the transmission of highly detailed 4K Ultra HD resolutions. With support for High-Dynamic Range, video content can be seen with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut, perfect for a true home cinema experience or eye-catching digital signage in retail settings. HDCP 2.2 compliance allows 4K video content from copy protected sources such as Blu-Ray movies, media players and streaming services to be viewed without compatibility issues. Support for lossless audio formats including DolbyTrueHD and DTS-HD adds powerful multi-channel sound to video content, providing an enhanced experience and sense of realism for the viewer.

The extender features an HDMI loop-through output on the transmitter which allows for simultaneous viewing using local and remote displays. This versatility provides a suitable solution for use in various scenarios such as educational presentation systems, home cinema, entertainment systems, or trade shows. The built in EDID dip switch enables the user to control which EDID is taken from either display, making installation and configuration simple ensuring maximum compatibility with HDMI displays and projectors. PoC allows both power and data signals over a Cat.6 cable in a point to point configuration, adding flexibility as only one power supply is required for both the transmitter and receiver units. Ideal when power outlets are limited.

Featuring IR Pass-through, the source equipment can be seamlessly controlled from the remote displays side of the installation using compatible infrared remote controls. This provides simple and complete control for the user.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.