

Link do produktu: <https://sosos.pl/io-hub-usb-c-6in1-sata-m2018m-hmc-6m2-axagon-p-40912.html>



I/O Hub USB-C 6IN1 Sata M.2/0.18M HMC-6M2 Axagon

Cena	186,72 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1438767
Kod EAN	8595247905796
Category Code	UHU
Szerokość opakowania wysyłkowego	10 cm
Wysokość opakowania wysyłkowego	22 cm
Unit Box Length	0.02
Rodzaj produktu	Rozdzielacz USB
Objętość jednostki brutto	1
ManufacturerCode	HMC-6M2
Wymiary	123 x 51 x 14 mm
Objętość brutto	0.00044 cubm
Jednostkowa waga brutto	0.12 kg
Głębokość opakowania wysyłkowego	2 cm
Waga opakowania wysyłkowego	0.12 kg
Unit Box Width	0.1
Unit Box Height	0.22
DDR3 1600/1333/1066/800	HMC-6M2
RJ46	1
Strona główna dostawcy	www.axagon.eu/en/produkty/hmc-6m2
Ilość w opakowaniu	1
Jednostkowa waga netto	0.072 kg
CnCode	85176200

Opis produktu

- Input:
- 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-C male connector.
 - Backward compatible with USB 3.1 Gen 1 / USB 3.0 and USB 2.0.
 - Compatible with Thunderbolt 3.

-
- Connecting USB type C male connector on a fixed 18 cm long cable.

USB outputs:

- 2x SuperSpeed USB port, USB-A female connector.
- 1x USB type C Power Delivery port (only for charging), USB-C female connector.
- Supports transmission rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
- The total bandwidth / transmission rate is determined by the USB 3.2 Gen 1 interface used (theor. 5 Gbit/s).
- USB-C hub handle the permanent connection of two external drives.

HDMI output:

- HDMI.
- HDMI A (F) female connector.
- Maximum supported resolution 4K / 4096 x 2160 at 30 Hz.
- DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output. Correct OS is also necessary. The video output function will not be available without these requirements.
- HPD (Hot-Plug-Detect) support.
- TMDS (Transition Minimized Differential Signalling) support.
- HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) support.
- Up to 8-channel LPCM audio, compressed audio (AC-3, DTC) and HBR audio format support.
- Sample rate up to 192 kHz and 24 bit audio support – depends on source and target device i.e. notebook/phone and TV/display/AV receiver.

RJ-45 output:

- Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
- Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
- Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
- 10/100/1000 Mbit/s auto-detection.
- Supports IPv4/IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/IGMP &