

Link do produktu: <https://sosos.pl/io-hub-usb-c-6in102m-hmc-6h4a-axagon-p-40911.html>



I/O Hub USB-C 6IN1/0.2M HMC-6H4A Axagon

Cena	127,12 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1438766
Kod EAN	8595247907028
Unit Box Width	0.1
Unit Box Height	0.2
DDR3 1600/1333/1066/800	HMC-6H4A
Objętość jednostki brutto	1
Strona główna dostawcy	www.axagon.eu/en/produkty/hmc-6h4a
Ilość w opakowaniu	1
Jednostkowa waga netto	0.054 kg
CnCode	85176200
Głębokość opakowania wysyłkowego	3 cm
Waga opakowania wysyłkowego	0.1 kg
Unit Box Length	0.03
Rodzaj produktu	Rozdzielacz USB
Architektura	3
ManufacturerCode	HMC-6H4A
Wymiary	110 x 35 x 13 mm
Objętność brutto	0.0006 cubm
Jednostkowa waga brutto	0.1 kg
Category Code	UHU
Szerokość opakowania wysyłkowego	10 cm
Wysokość opakowania wysyłkowego	20 cm

Opis produktu

- Input:
- 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-C male connector.
 - Backward compatible with USB 3.1 Gen 1 / USB 3.0 and USB 2.0.
 - Compatible with Thunderbolt 3.

-
- Connecting USB type C male connector on a fixed 20cm long cable.

USB outputs:

- 4x SuperSpeed USB port, USB-A female connector.
- 1x USB type C Power Delivery port (only charging), USB-C female connector.
- Supports transmission rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
- The total bandwidth / transmission rate of the box is determined by the USB 3.2 Gen 1 interface used (theoretically up to 5 Gbit/s).
- USB-C hub can handle the connection of several external drives at the same time.

HDMI output:

- HDMI.
- HDMI A (F) female connector.
- Maximum supported resolution 4K / 4096 x 2160 at 30 Hz.
- WQHD resolution 2560 x 1440 at 60 Hz max.
- FullHD resolution 1920 x 1080 at 60, 100, 120 Hz max.
- DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output. At the same time, support from the device (laptop, phone) and the operating system is required. The video output function will not be available without these requirements.
- HPD (Hot-Plug-Detect) support.
- TMDS (Transition Minimized Differential Signalling) support.
- HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) support.
- Support up to 8-channel LPCM audio, compressed audio (AC-3, DTS) and HBR audio formats.
- Support sampling rate up to 192kHz and up to 24-bit audio – depends on source and end device, i.e. laptop/phone and TV/monitor/ AV receiver.

Power Delivery:

- Power Delivery 3.0 support – device power supply from the wall charger via USB-C hub.
- Maximum power supply power via PD USB-C hub output 100W - 20V/5A.
- Required PD support from the device (laptop, phone) and a suitable PD wall charger.

Other features:

- Possibility to connect your device while running thanks to the Hot Plug support.
- Full Plug and Play support.
- Standby mode support.
- Power via USB bus - USB bus power or from PD wall charger.
- Heavy-duty aluminum body for better hub cooling. Higher surface hub temperature is not a problem - the heat generated by the hub operation is better dissipated and transferred to the surroundings.
- The backlight of the logo indicates with a permanent glow that the hub is connected to the computer.
- The high quality shielded cable ensures high communication speed and minimal undesirable interference.
- Dimensions 110 x 35 x 12 mm.
- Weight 54 g (incl. cable).
- USB cable length 20 cm.

Supported operating systems:

- Microsoft Windows 10 / 11, Mac OS, Linux, Android and Chrome OS.

Compatibility depends on used OS and support from device manufacturer.

Note 1: Drivers are included with supported operating systems and are installed automatically. No other drivers need to be installed.

Note 2: DisplayPort Alternate Mode (DP Alt Mode) is only supported in updated OS and also depends on support from device (notebook, phone) manufacturer.

Package contains:

- USB-C hub with fixed 20 cm long cable,
- multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box with a hanging hole.