

Link do produktu: <https://sosos.pl/io-kvm-extender-ps2usb-300m39378-lindy-p-35206.html>

I/O Kvm Extender PS/2&USB 300M/39378 Lindy

Cena	1 574,79 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1431472
Kod EAN	4002888393782
Category Code	IOC
Szerokość opakowania wysyłkowego	14 cm
Wysokość opakowania wysyłkowego	17.5 cm
Unit Box Length	0.205
Rodzaj produktu	Extender
Dołączone akcesoria	Transmitter UnitReceiver Unit2 x 3-in-1 KVM cable, 1.2m2 x USB to PS/2 adapter1 x USB Type A/B cable, 1.2m2 x Multi-Country Power Supply (EU, UK, US, AUS)Lindy Manual
Strona główna dostawcy	www.lindy.eu/300m-Cat-6-VG-A-USB-PS-2-KVM-Extender-Combo.htm?websale8=Id0101.Id021102&pi=39378
15pin D-sub	1
Wymiary	130 x 70 x 28 mm
Objętość brutto	0.005023 cubm
Jednostkowa waga brutto	1.79 kg
Głębokość opakowania wysyłkowego	20.5 cm
Waga opakowania wysyłkowego	1.67 kg
Unit Box Width	0.14
Unit Box Height	0.175
DDR3 1600/1333/1066/800	39378
ManufacturerCode	39378
RJ46	1
USB 2.1	2
PS/3	2

Ilość w opakowaniu	1
Jednostkowa waga netto	0.3 kg
CnCode	85176200

Opis produktu

300m Cat.6 VGA, USB & PS/2 KVM Extender Combo
Extend VGA, USB or PS/2 over a Cat.6 cable

- Extends VGA, USB and PS/2 up to 300m using a single Cat.6 cable
- Supports VGA resolutions up to 1920x1200
- Dual console operation - control your computer / KVM Switch from both local and remote locations
- Easy, user friendly installation - no software required
- 2 year warranty

The Lindy Cat.6 VGA, USB & PS/2 KVM Extender allows users to control a source device such as a PC from a single keyboard, mouse and display up to 300m using a Cat.5e/6 RJ45 cable. Supports analogue resolutions up to 1920x1200 with VGA ports, ideal for managing a PC or workstation from very long distances. The Extender features PC & console ports on the transmitter to connect additional display, keyboard and mouse for local control and console & PC ports on the receiver to connect an additional PC on the remote console side. In both units you can either connect USB or PS/2 keyboard and mouse and PCs using the KVM cables included. It's also possible to connect a second source on the receiver unit and control it pushing the switching button on the front panel or via hotkey. Via OSD menu users can adjust video signal, EDID, enable password protection and change hotkeys.

This extender provides a simple plug & play installation, no additional drivers required, great for both professional and first time users.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.