

Link do produktu: <https://sosos.pl/wrl-access-pointu6-pro-ubiquiti-p-41420.html>

Wrl Access POINT/U6-PRO Ubiquiti

Cena	714,47 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1362224
Kod EAN	810010076830
Jednostkowa waga brutto	1 kg
Category Code	WAP
Szerokość opakowania wysyłkowego	25 cm
Wysokość opakowania wysyłkowego	5 cm
Unit Box Length	0.25
Rozmiar czujnika	44 to 57VDC, 13W
Typ urządzenia sieciowego	Bezprzewodowy punkt dostępu
Strona główna dostawcy	eu.store.ui.com/products/uni-fi-ap6-professional
Typ anteny	Wielokierunkowy
Wymiary	Ø197 x 35 mm
Szybkość transmisji danych	4800 Mbps
Objętość brutto	0.003125 cubm
CnCode	85176200
Głębokość opakowania wysyłkowego	25 cm
Waga opakowania wysyłkowego	1 kg
Unit Box Width	0.25
Unit Box Height	0.05
DDR3 1375	2.4 and 5 GHz
ManufacturerCode	U6-PRO
10Base-T / 100Base-TX / 1000Base-T	1
Nazwa modelu	UniFi6 Pro
Zysk energetyczny anteny	6 dB
Ilość w opakowaniu	1
Jednostkowa waga netto	0.46 kg

Opis produktu

UBIQUITI UniFi6 Pro

Indoor, dual-band WiFi 6 access point that can support over 300 clients with its 5.3 Gbps aggregate throughput rate.

The UniFi6 Pro (U6 Pro) is a high-performance, dual-band WiFi 6 access point ideal for home and office use. The U6 Pro is capable of reaching an aggregate throughput rate up to 5.3 Gbps with its 5 GHz (4x4 MU-MIMO and OFDMA) and 2.4 GHz (2x2 MU-MIMO and OFDMA) bands, which allows it to support over 300 concurrently connected clients while maintaining an even, reliable wireless experience across your entire network. It can also isolate your guest traffic to ensure optimal security and speed. The U6 Pro also operates at full 4x4 MIMO with 160 MHz channels to create high-capacity wireless uplinks and facilitate faster data transfer. It can be set up in minutes and fully managed with the UniFi Network application.

Features:

Dual-band WiFi 6 (802.11ax)

5 GHz (4x4 MU-MIMO and OFDMA) band with a 4.8 Gbps throughput rate

2.4 GHz (2x2 MU-MIMO and OFDMA) band with a 573.5 Mbps throughput rate

Operates at full 4x4 MIMO with 160 MHz bandwidth

300+ concurrent client capacity

Guest Traffic Isolation, which enhances wireless network security and lowers traffic congestion

Included universal mounting plate, backing plate, and screw kit