

Link do produktu: <https://sosos.pl/zasilacz-atx231-650wgp-p650ss-gigabyte-p-38400.html>



Zasilacz ATX2.31 650W/GP-P650SS Gigabyte

Cena	232,81 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1421061
Kod EAN	4719331554095
Dostępne instrukcje	12cm fan
Nazwa modelu	GP-P650SS
Ilość w opakowaniu	5
Jednostkowa waga netto	2.1 kg
CnCode	85044095
Głębokość opakowania wysyłkowego	61.5 cm
Waga opakowania wysyłkowego	11.2 kg
Unit Box Width	0.21
Unit Box Height	0.12
Zasilacz	ATX 3.0
ManufacturerCode	GP-P650SS
Strona główna dostawcy	GIGABYTE P650SS
Wymiary	150 x 140 x 86 mm
Objętość brutto	0.007577 cubm
Jednostkowa waga brutto	2.24 kg
Category Code	PSU
Szerokość opakowania wysyłkowego	22 cm
Wysokość opakowania wysyłkowego	28 cm
Unit Box Length	0.255
Kolor	Czarny
Moc wyjściowa zasilacza	650 Watts

Opis produktu

- GIGABYTE P650SS
- + 80 PLUS Silver certified (230V EU)
 - + Support Intel ATX 3.0 standard

-
- + 120mm Fluid Dynamic Bearing (FDB) Fan
 - + Flat cable design
 - + Powerful single +12V rail
 - + OVP/OPP/SCP/UVF/OCP/OTP protection

80 PLUS SILVER CERTIFIED

The 80 Plus Silver certification (230V EU) guarantees a 90% efficiency rate at a 50% load, resulting in reduced power wastage, diminished heat generation, and minimized fan noise.

Support Intel ATX 3.0 standard

The P650SS can sustain up to 2x total power excursion. It is fully compatible with Intel PSDG (Power Supply Design Guide) ATX 3.0 standard which supports up to 200% power excursion, reaches 70% low load efficiency and complies with required power supply timing standards.

120MM FLUID DYNAMIC BEARING(FDB) FAN

High-performance Fluid Dynamic Bearing fan uses oil film shock absorption technology to effectively reduce noise, making it quieter than conventional sleeve fan and providing more than twice the lifespan. In addition, the fan will detect the current power usage and temperature, automatically adjust the fan speed to minimize the noise.

RELIABLE FLAT CABLE DESIGN

The utilization of flat cables minimizes clutter while enhancing the thermal performance of the chassis.

SINGLE +12V RAIL

The single +12V rail delivers optimal power output, stability, and hardware compatibility. This design not only simplifies power cable installation but also stands as the most effective choice for overclocking purposes.

PROTECTION

To guarantee the stable operation of your entire computer system under any circumstances, we have incorporated a range of protective features including OCP, OTP, OVP, OPP, UVP, and SCP. Moreover, we have obtained safety certifications from various countries to ensure the consistent and secure functioning of your system.