

Link do produktu: <https://sosos.pl/zasilacz-atx231-750wgp-p750gm-gigabyte-p-38403.html>



Zasilacz ATX2.31 750W/GP-P750GM Gigabyte

Cena	349,99 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	1306555
Kod EAN	4719331551759
Głębokość opakowania wysyłkowego	61 cm
Waga opakowania wysyłkowego	13.16 kg
Unit Box Width	0.12
Unit Box Height	0.21
Zasilacz	ATX 2.31
ManufacturerCode	GP-P750GM
MTBF	100000 GODZINY
Nazwa modelu	GP-P750GM
DDR 400/ECC	Aktywny
Ilość w opakowaniu	5
Jednostkowa waga netto	2 kg
CnCode	85044095
Szerokość opakowania wysyłkowego	23 cm
Wysokość opakowania wysyłkowego	29 cm
Unit Box Length	0.255
Kolor	Czarny
Moc wyjściowa zasilacza	750 Watts
Strona główna dostawcy	www.gigabyte.com/Power-Supply/GP-P750GM#kf
Dostępne instrukcje	12cm fan
Wymiary	150 x 140 x 86 mm
Gniazdo mikrofonu 3,5 mm	80 PLUS GOLD
Objętość brutto	0.008137 cubm
Jednostkowa waga brutto	2.63 kg
Category Code	PSU

Opis produktu

GIGABYTE P750GM

Power Supply

- + 80 PLUS Gold certified
- + Fully modular design
- + 120mm Smart Hydraulic Bearing (HYB) Fan
- + Main Japanese capacitors
- + Powerful single +12V rail
- + OVP/OPP/SCP/UEP/OCP/OTP protection
- + Compact size

Connectors:

- + ATX/MB 20+4 Pin x 1
- + CPU/EPS 4+4 Pin x 2
- + PCI-e 6+2 Pin x 4
- + SATA x 8
- + 4 Pin Peripheral x 3 + 4-Pin floppy x 1

FULLY MODULAR DESIGN

All the black flat cables are modular design. Installing only the cables you need to reduce clutter, to increase the airflow and to improve the chassis thermal performance.

80 PLUS GOLD CERTIFIED

80 Plus Gold certified ensures to deliver 90% efficiency at 50% load. The better power efficiency leads to less power waste, less heat and less fan noise. And with the support of Intel processors, it will save more energy and more money.

HIGH QUALITY JAPANESE CAPACITORS

The main capacitors are high quality Japanese capacitors, to produce the efficient performance and to ensure the longer reliability.

120MM SMART HYDRAULIC BEARING (HYB) FAN

The fan speed is adjusted according to the automatic power detection and will stop when the system is idle or under low load (less than 20% load). The Hydraulic Bearing fan provides longer and more stable life time.